

[Equipment]

Wertheim offers several equipment variations. The standard are adjustable shelves (quantities depending on model height). Other equipment available optionally.

Note, that the shown equipment variations depend on safe models. Kindly check the respective safe type page.



[Shelf]

The shelf with a loading capacity of 20 kg can be variably adjusted in each spacing and enables an individual interior design. Shelves for higher loads upon request. Spacing:

AG, AM, AP, BG, BM, BP, CM, CP, VA, VB, VBE:	85 mm
AWS, BWS:	60 mm (models 1500: 90 mm)
AMS:	80 mm
CWS-DWS(KB)-EWS(KB) 0849:	60 mm
CWS-DWS(KB)-EWS(KB) from 0850 up, BWP:	69 mm



[Drawer ¹]

The drawer with a loading capacity of 45 kg is available in different heights depending on the safe model.

AG, AM, AP, BG, BM, BP, CM, CP, VB, VBE:	80 or 165 mm inside height
CWS-DWS(KB)-EWS(KB) from 0850 up, BWP:	85 or 175 mm inside height



[Drawer lockable ¹]

The drawer with a loading capacity of 45 kg is lockable with key lock and is available in different heights depending on the safe model.


AG, AM, AP, BG, BM, BP, CM, CP, VB, VBE:	65 or 150 mm inside height
CWS-DWS(KB)-EWS(KB) from 0850 up, BWP:	70 or 160 mm inside height
CWP:	134 mm inside height



[Pull-out shelf ¹]

The pull-out shelf offers a loading capacity of 45 kg. Height division:

AG, AM, AP, BG, BM, BP, CM, CP, VB, VBE:	85 mm
CWS-DWS(KB)-EWS(KB) from 0850 up, BWP:	90 mm
CWP:	min. 155 mm (120 kg capacity)



[Necessary wall distance in case of drawer / pull-out shelf]

AG, BG	D = 300 mm	C-D-EWS(KB) 0850-1901	D = 530 mm
AM, BM	D = 375 mm	C-D-EWS(KB) 1903	D = 740 mm
AP, BP, CP	D = 325 mm	C-D-EWS(KB) 1902 ^{*)}	D = 530 mm
BP41	D = 475 mm		D1 = 220 mm
CM 15-25	D = 360 mm	C-D-EWS(KB) 1904 ^{*)}	D = 530 mm
CM 30-40	D = 475 mm		D1 = 440 mm
VB, VBE	D = 85 mm		

^{*)} D1: left wall distance in case of double-doored safes



Fig. AM30



Fig. BG35



Fig. CM15



[Inside locker ²]

The inside locker is lockable with key lock and is available in different heights, one- or double-doored depending on the safe model.

AG, AM, AP, BG, BM, BP, CM, CP, VB, VBE:	1-doored, 170 or 340 mm high
AWS, BWS:	2-doored, 180 or 360 mm high
AMS:	1-doored, 180 mm high
CWS-DWS(KB)-EWS(KB) 0849:	1-doored, 180 or 360 mm high
CWS-DWS(KB)-EWS(KB) from 0850 up, BWP:	2-d. or 2x1-d., 240 or 360 mm high



[Key rack ³]

The key rack with 8 hooks (models CM30, CM35, CM40 with 10 hooks) can be attached to the inside of the safe door at different positions, depending on the safe model. Possible pieces due to safe model:

03: max. 1 pc.	15: max. 4 pcs.	30: max. 10 pcs.
05: max. 1 pc.	20: max. 6 pcs.	35: max. 12 pcs.
10: max. 2 pcs.	25: max. 8 pcs.	40: max. 14 pcs.

¹ Please note the necessary wall distance (hinge side) when installing the safe. When placing the drawer/pull-out shelf on top position, there is no possibility of alarm connection and alarm switch set at safes grade I, II and safe type CP.

Drawers/pull-out shelves for higher loads at safe types CWS, DWS(KB), EWS(KB), BWP upon request. Equipment variations for type CWP upon request.

The key of drawers must be removed before closing the safe door, because otherwise closing is not possible.

² Please note, that inside lockers don't offer enough depth for file folders – except safe types AWS, BWS, BWP and CWS-DWS(KB)-EWS(KB) from safe model 0850 up.

In case of 2x1-doored version the inside lockers are besides each other.

³ In the height of drawers you can't use key racks on the inside of the safe door.