



EN1143-1
Burglary protection

VdS
Grade III

ECB-S
Grade III

ISO
Class EN 3

A2B
Class III E
(except K-Lock Secu)

DIN
4102 (light fire protection)

Domestic insurable
up to EUR 200.000

Commercial insurable
up to EUR 100.000

Fig. Swing-in door safe CWP0901, hinge right
K-Lock Secu 2 keys (125 mm), 1 lockable drawer, 2 pull-out shelves

[Swing-in door safes – desk safes]

[Type CWP]

CWP series safes are fitted with swing-in doors and make working with the door open easy. The dimensions are chosen to enable an installation under a desk making it ideal for use in small areas.

[Product information]

Hinge	DIN right – model designation R (CWP0652, CWP0902 double-doored)
Door opening	swing-in doors – upon opening, the doors slide into the side of the safe, leaving the area in front of the safe completely free – several safes can be positioned next to each other in a row, without open doors interfering each other
Body	triple-walled, reinforced, filled with armoured, high resistant barrier material
Door structure	triple-walled, reinforced, filled with armoured, high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
Locking mechanism	three-way moving boltwork with large steel bolts protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side
Anchoring	fitted for floor anchoring anchoring bolts and shields are supplied option: additional anchoring holes (customer specifies position)
Alarm connection	VdS-certified cable channels to allow connection to a burglar alarm system
Colour	inside and outside RAL 7035 light grey option: special colour according to RAL
Lock	model designation K – double-bit lock VdS class 2, Secu 2 keys (125 mm) model designation E – electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary lock)
Equipment	option: lockable drawer, pull-out shelf, cashier equipment Inkiess lowest pull-out shelf with automatic push-out (100 mm)
Accessories	option: alarm switch set, interior lighting
Option	electronic drawer control, version multisafe certified in accordance with VdS 2450 grade III (SE105301)

[Cashier equipment Inkiess 880PL]


Cashier equipment consists of coin trays, coin and note boxes, full details upon request.



Fig. Cashier equipment Inkiess 880PL

[Electronic drawer control]

Fig. keypad input unit



Swing-in door safes, equipped with electronic controlled drawers, take today's requests of modern bank organisation into account. Different access entitlements to the safe facilities can be organized and changed any time in a very simple way.

The operation of the drawers as well as programming the opening codes is possible via keypad input unit with a 4-digit code on an easy to read display. The keypad is built in even into the desktop.

- Unlocking a drawer by input of a 4-digit, programmable opening code
- Individual drawers have facility of time delayed opening
- Adjustable drawer activation time
- Attack alarm activation which allows the drawer opening by input of the attack/duress alarm

Model	Outside dimensions		Inside dimensions		Volume (l)	Weight (appr. kg)
	h	w x d (mm)	h	w x d (mm)		
CWP0651RK / CWP0651RE	648	850 x 754	486	514 x 590	147	515
CWP0901RK / CWP0901RE	878	850 x 754	716	514 x 590	217	635
CWP0652K / CWP0652E	648	1308 x 754	486	820 x 590	235	730
CWP0902K / CWP0902E	878	1308 x 754	716	820 x 590	346	890

Please add 20 mm to the listed outside depth for mountings.