





Fig. Safe DWS1200KB, hinge right
2 x N-Lock La Gard 3390VZ (3 wheels), 2 shelves

-  EN1143-1
Burglary protection
-  EN15659
Fire protection (option)
-  VdS
Grade IVKB
-  ECB-S
Grade IVKB
+ LFS60P (option)
-  ISO
Class EN 5
-  DIN
4102 (light fire protection)

-  Domestic insurable
by arrangement
-  Commercial insurable
up to EUR 250.000

[Safes]

[Type DWSKB]

In addition to the DWS series features, DWSKB series safes provide additional protection against burglars armed with diamond core drills thanks to their special structural wall design. Safes weighing less than 1.000 kg must be anchored.

[Product information]

- Hinge** DIN right – model designation R (DWS1902KB, DWS1904KB double-doored)
option: DIN left
- Door opening angle** 180°
- Body** double-walled, reinforced, with core drill protection, filled with armoured, high resistant barrier material
- Door structure** triple-walled, reinforced, with core drill protection, with armoured, high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
- Locking mechanism** three-way moving boltwork with large steel bolts, protected by glass plate with additional emergency re-locks, fix engaging steel bolts on the hinge side
- Anchoring** fitted for floor anchoring
anchoring bolts and shields are supplied for DWS0849KB, DWS0850KB
option: additional anchoring holes (customer specifies position)
- Alarm connection** VdS-certified cable channels to allow connection to a burglar alarm system
- Colour** outside RAL 7035 light grey + RAL 7045 tele grey1, inside RAL 7035 light grey
option: special colour according to RAL
- Lock** safes in grades IV and higher have to be equipped with at least 2 certified locks
any set of locks (from VdS class 2 up) is possible
- Equipment** shelf adjustable (height setting 69 mm, DWS0849 60 mm)
option: additional shelf, inside locker
option (from DWS0850KB up): drawer, pull-out shelf
- Accessories** option: fire protection door rebate seals, alarm switch set, interior lighting
- Option** additional certified fire protection LFS60P – except models:
DWS0849KB, DWS1902KB, DWS1904KB
bolted version – assembly on site
from Model DWS1000KB up (not possible in combination with certified fire protection)

Model	Outside dimensions		Inside dimensions		SH	Volume (l)	Weight (appr. kg)
	h	x w x d (mm)	h	x w x d (mm)			
DWS0849KBR	848	x 645 x 565	695	x 495 x 320	1	110	635
DWS0850KBR	848	x 810 x 725	695	x 660 x 480	1	220	875
DWS1000KBR	1003	x 810 x 725	850	x 660 x 480	2	269	1030
DWS1200KBR	1193	x 810 x 725	1040	x 660 x 480	2	329	1150
DWS1600KBR	1538	x 810 x 725	1385	x 660 x 480	3	439	1405
DWS1901KBR	1883	x 810 x 725	1730	x 660 x 480	4	548	1680
DWS1903KBR	1883	x 1110 x 725	1730	x 960 x 480	4	797	2090
DWS1902KB	1883	x 1110 x 725	1730	x 960 x 480	4	797	2130
DWS1904KB	1883	x 1415 x 725	1730	x 1265 x 480	4	1050	2550

SH = Shelf

Please add 60 mm to the listed outside depth for mountings.

[Equipment options]

